

## **Bygg- & Elhandsågsklingor. / Construction Saw Blades.**

*Dessa klingor tillverkas med samma höga krav på funktion och kvalitet som vårt övriga sortiment. Stambladet är tillverkat i höglegerat, härdat stål som tål vridningar och ger ett rakt snitt. Klingorna levereras med tandform BA, är av industrikvalitet och kan slipas om 15-20 gånger beroende på användningssätt. Skall inte förväxlas med de lågkvalitetsprodukter som finns på marknaden idag.*

*These blades are manufactured to the same high standards of function and quality as the rest of our product range. The body of the blade is made from high alloy, hardened steel that withstands high torsional stresses and ensures a straight cut. The blades are supplied with BA tips, are of industrial quality and can be re-sharpened about 15-20 times depending on how they are used. Shall not be mixed up with the low quality products that are on the market today.*



PROFESSIONELL hårdmetallklinga för elektriska handsågar, tillverkade av härdat stål och med hårdmetalltänder som kan slipas om 15-20 gånger. Avsedd för kapning och formatsågning.

PROFESSIONAL carbide tipped blade for electric hand saws, made from hardened steel with Hm carbide teeth that can be re-sharpened 15-20 times. Intended for crosscutting and panel sizing.

Id	Std.	Art no	Type	Info
1466	x	18613	10BA20P-125-2,3/1,5-20	Z=20
1467	x	22132	10BA20P-152-2,5/1,5-20	Z=24
1468	x	21991	10BA20P-160-2,5/1,5-20	Z=24
1469	x	21934	10BA20P-165-2,5/1,5-30	Z=24
1470	x	23122	10BA20P-170-2,5/1,5-16	Z=28
1471	x	22499	10BA20P-180-2,5/1,5-20	Z=28
1472	x	22558	10BA20P-180-2,5/1,5-30	Z=28
1473	x	22221	10BA20P-185-2,5/1,5-30	Z=28
1474	x	22459	10BA20P-190-2,5/1,5-30	Z=32
1475	x	23900	10BA20P-210-2,8/1,8-30	Z=32
1476	x	23901	10BA20P-210-2,8/1,8-34,9	Z=32
1477		18415	10BA20P-210-3,0/2,0-30	Z=32 P=2/7/42
1478	x	24088	10BA20P-235-2,8/1,8-30	Z=36
1479	x	23056	10BA20P-235-2,8/1,8-34,9	Z=36
1480		15484	10BA20P-235-3,0/2,0-16	Z=36

Id	Std.	Art no	Type	Info
1481		15499	20BA28P-125-2,3/1,5-20	Z=12
1482	x	22528	20BA28P-152-2,5/1,5-20	Z=16
1483		15731	20BA28P-155-2,3/1,5-12,7	Z=16
1484		35864	20BA28P-155-2,3/1,5-20	Z=16
1485	x	22986	20BA28P-160-2,5/1,5-20	Z=16
1487	x	23902	20BA28P-165-2,5/1,5-30	Z=16
1488	x	23395	20BA28P-170-2,5/1,5-30	Z=20
1489		35869	20BA28P-180-2,0/1,5-40	Z=20 P=2/7/42
1490		15707	20BA28P-180-2,3/1,5-30	Z=20 P=2/7/42
1491	x	23208	20BA28P-180-2,5/1,5-20	Z=20
1492		27494	20BA28P-180-2,5/1,5-20,64	Z=20 S=3/8/105,5/11//L
1493		39007	20BA28P-180-2,5/1,5-20,64	Z=20 S=3/7/51,6/10/L
1494	x	23903	20BA28P-180-2,5/1,5-30	Z=20
1495	x	22585	20BA28P-190-2,5/1,5-30	Z=24
1496	x	23904	20BA28P-200-2,5/1,5-30	Z=24
1497	x	23472	20BA28P-210-2,8/1,8-30	Z=24
1498	x	23905	20BA28P-210-2,8/1,8-34,9	Z=24
1499		15493	20BA28P-210-3,0/2,0-30	Z=24 P=2/7/42
1500	x	23906	20BA28P-220-2,8/1,8-30	Z=28
1501	x	22313	20BA28P-230-2,8/1,8-30	Z=28
1502	x	23209	20BA28P-235-2,8/1,8-30	Z=28

X = Lager std. X = Stock std.



Hårdmetallsågklinga avsedd för stationära byggsågar.

Carbide tipped blade intended for fixed construction saws.

Id	Std.	Art no	Type	Info
1503		40953	20BA24Y-315-3,2/2,2-30	Z=40
1504		17026	20BA26Y-300-2,8/2,0-20	Z=36
1505	x	23885	20BA26Y-300-2,8/2,0-30	Z=36 P=2/10/60+2/7/42
1506	x	22142	20BA26Y-350-3,2/2,2-30	Z=42 P=2/10/60+2/7/42
1507	x	17703	20BA26Y-400-3,2/2,2-25	Z=48
1508		23886	20BA26Y-400-3,2/2,2-30	Z=48 P=2/10/60

Id	Std.	Art no	Type	Info
1509		17038	20BA30Y-200-2,8/1,8-30	Z=20
1510		16679	20BA30Y-200-2,8/2,0-20	Z=20
1511	x	23098	20BA30Y-250-2,8/2,0-30	Z=24 P=2/10/60+2/7/42+2/9/46
1512	x	23099	20BA30Y-300-3,2/2,2-30	Z=30 P=2/10/60+2/7/42+2/9/46
1513		26180	20BA30Y-300-3,2/2,2-35	Z=30 P=2/10/60 + 2/7/42
1514	x	23100	20BA30Y-315-3,2/2,2-30	Z=30 P=2/10/60+2/7/42+2/9/46
1515	x	23101	20BA30Y-350-3,5/2,2-30	Z=36 P=2/10/60+2/7/42
1516		20615	20BA30Y-350-3,5/2,2-35	Z=36
1517	x	17707	20BA30Y-400-3,5/2,2-25	Z=40
1518	x	22057	20BA30Y-400-3,5/2,2-30	Z=40 P=2/10/60+2/7/42
1519		20616	20BA30Y-400-3,5/2,2-35	Z=40
1520		34742	20BA30Y-400-3,5/2,2-45	Z=40
1521		20758	20BA30Y-400-3,5/2,2-50	Z=40
1522	x	19576	20BA30Y-450-4,0/2,8-30	Z=44
1523		36606	20BA30Y-450-4,0/2,8-35	Z=44
1524		34209	20BA30Y-450-4,0/2,8-40	Z=44
1525		20491	20BA30Y-500-4,0/2,8-30	Z=50



SPECIALKLINGOR med negativ skärvinkel för ELU / DeWalt maskiner.

Special blades with negative (N) rake angle for ELU/DeWalt saws.

Id	Std.	Art no	Type	Info
1526	x	18606	N05BA10P-216-2,8/2,0-30	Z=64
1528	x	16603	N05BA13P-216-2,8/2,0-30	Z=48
1537	x	20135	N08BA26P-216-2,8/1,8-30	Z=24



*Något du inte hittar i katalogen?  
Ring oss direkt eller skicka din förfrågan.  
Vårt sortiment omfattar mycket mer än det du ser i katalogen.*

*Something you don't find?  
Please call us immediately or send us your inquiry.  
Our product range includes much more than what we can show  
in the catalogue.*